

LITHIUM SECONDARY BATTERY AND METHOD OF MANUFACTURING THE SAME

Publication number: JP2002373707 (A)

Publication date: 2002-12-26

Inventor(s): MORI MITSUHIRO; UTSUKI KOJI; YAMAMOTO HIROCHIKA;
IRIYAMA JIRO; MIURA TAMAKI

Applicant(s): NIPPON ELECTRIC CO

Classification:

- international: H01M10/40; H01M4/02; H01M4/04; H01M4/38; H01M4/40;
H01M4/58; H01M4/62; H01M10/36; H01M10/38; H01M10/36;
H01M4/02; H01M4/04; H01M4/38; H01M4/40; H01M4/58;
H01M4/62; (IPC1-7): H01M10/40; H01M4/02; H01M4/40;
H01M4/62

- European: H01M10/0565; H01M4/02B; H01M4/04C4; H01M4/38;
H01M4/40; H01M10/052; H01M10/0582; H01M10/0565

Application number: JP20010180710 20010614

Priority number(s): JP20010180710 20010614


Also published as:

US2003003364 (A1)
KR20020095448 (A)
CN1382624 (A)
CN1199309 (C)

3

Abstract of JP 2002373707 (A)

PROBLEM TO BE SOLVED: To provide a lithium secondary battery using lithium metal as negative electrode active material, hard to generate dendrites, and excellent in cycle life and security. SOLUTION: The negative electrode of the lithium secondary battery is an electrode obtained by forming a film of an amorphous lithium metal or amorphous lithium alloy on at least one kind of lithium ion support layer formed in the shape of a sheet. For the lithium ion support layer, a thin film of a vitreous solid electrolyte, a polymer solid electrolyte, a carbon material, or a lithium halogen compound, or a polyolefinic porous membrane, is used.



Data supplied from the esp@cenet database — Worldwide